




HASO

MULTISPECTRAL

Wavefront sensor
The Polychromatic

Spatio-temporal characterization
Easy & fast to use
Broad spectral range



HASO MULTISPECTRAL +

The HASO MULTISPECTRAL is an excellent choice for most laboratories and large installations. It is Imagine Optic's proposal for direct spectrally-resolved wavefront measurement, ideal for compressor alignment.

This innovation is based on the proven Shack-Hartmann wavefront sensing technology.

APPLICATIONS


HASO MULTISPECTRAL is the first-ever wavefront sensor on the market capable of resolving frequency on a broad spectral range from 550 - 1000 nm. Coupled with our standard HASO BROADBAND, it allows a complete characterization of TW and PW class lasers in order to optimize the peak intensity on the target.

This new device is perfectly suited for:

- + Compressor alignment
- + Characterization of compressed or stretched beams
- + Alignment of complex broadband systems
- + Understanding spatio-temporal coupling
- + Precise measurement of spatial chirp, chromatic curvature

FEATURES

- + Fast measurement and direct post-processing
- + Compatible with compressed or stretched pulses
- + Nanometric spectral resolution
- + Handles very short laser pulses down to ~ 5 fs
- + Compatible with lowest repetition rates, ex. 0.1 Hz
- + Removable HASO BROADBAND for standalone use
- + Optional exchangeable collimating optics (contact us for available N.A. adapted to your laser beam)



SPECIFICATIONS*

HASO MULTISPECTRAL OPERATING SPECS

Input beam	collimated (default) or any F/# (option)
Aperture dimension	5.0 x 5.0 mm ²
Calibrated wavelength range	550 - 1000 nm
Spectral resolution	1 nm

MISC

Dimensions (Height x Width x Length)	80 x 262 x 280 x mm ³
Weight for USB version	4 kg
Working temperature	15 - 30 °C
Interface	Ethernet or USB 3.0

EMBEDDED HASO BROADBAND OPERATING SPECS


Aperture dimension	6.9 x 5.1 mm ²
Number of microlenses	68 x 50
Maximum acquisition frequency	58 Hz (USB 3.0) or 30 Hz (with GigE converter)
Calibrated wavelength range	350 - 1100 nm
Minimum power	0.15 nW
External trigger	TTL signal
Operating system	Windows 10 & 11

OPTICAL SPECS

Repeatability	< $\lambda/200$ RMS
Absolute wavefront measurement accuracy	
• λ between 350-600 nm	≤ 6 nm RMS
• λ between 600-1100 nm	$\sim \lambda/100$ RMS
Spatial sampling	$\sim 105 \mu\text{m}$
Local radius of curvature dynamic range	± 0.010 m to $\pm \infty$

MISC

Dimensions (Height x Width x Length)	42 x 47 x 60 mm ³
Weight	200 g
Working temperature	15 - 30 °C
Interface	USB 3.0 or optional GigE converter
Power consumption	3.1 W



*Subject to changes without further notice

MODULARITY


- + HASO MULTISPECTRAL is designed to be easy to set up and align. Only an attenuated 5 mm collimated beam is required as input. Any NA can be handled by adding an optional module
- + With its self-aligning magnetic mount, HASO WFS can be easily used as a stand-alone sensor for diagnostic purposes, or to monitor an adaptive optic loop. Once repositioned on the MULTISPECTRAL platform, it is instantly realigned with SpotTracker™



SOFTWARE

MULTISPECTRALVIEW™ Metrology Software

- + MULTISPECTRALVIEW™ is our dedicated software for spatio-temporal coupling analysis
- + It enables the alignment of the device and a complete and direct characterization of the beam



CONTACT US

Imagine Optic Headquarters
18, rue Charles de Gaulle
91400 ORSAY · France
Phone +33 (0)1 64 86 15 60
sales@imagine-optic.com
www.imagine-optic.com

